

**Technical Data sheet**

**SODIUM SELENITE GMP**

**Product Code :**352502 SODIUM SELENITE GMP

**Formula :**Na<sub>2</sub>SeO<sub>3</sub>

**Retest period :** 24 months

**Standard Grade :** PE

**Rev.:** 20/11/2017

**According to monographs :**PH.EUR. 9ED.

**General Information :**

Mol weight	172,94 g/mol
CAS Nr	10102-18-8
C.E.E. Nr	034-002-00-8
EINECS Nr	233-267-9
HS code	28429010

**Transport :**

ADR/RID Class	6.1/I,T5
UN Nr	2630
Danger	66
Transport Labels	6.1 N
IMDG Code	6.1/I
IATA Code	6.1
IATA Group	I
CAO Code	673
PAX Code	666

**Specifications :**

Identification A	Passes test	Identification B	Passes test
Identification C	Passes test	Identification D	Passes test
Assay(Iodim.,dried basis)	98,5 - 101,5 %	Appearance of solution	Passes test
Chloride (Cl)	Max. 50,0 ppm	Loss on drying at 130°C	Max. 0,5 %
pH disolución al 10%	9,8 - 10,8	Sulfates and selenates	Max. 300,0 ppm
Iron (Fe)	Max. 50,0 ppm	Arsenic (As)	Max. 1,0 ppm

**Labels :** H-300:Fatal if swallowed. H-330:Fatal if inhaled. H-EUH031:Contact with acids liberates toxic gas. H-315:Causes skin irritation. H-317:May cause an allergic skin reaction. H-319:Causes serious eye irritation. H-411:Toxic to aquatic life with long lasting effects. P-301+310:IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P-304+340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P-280:Wear protective gloves/protective clothing/eye protection/face protection. P-261:Avoid breathing dust/fume/gas/mist/vapours/spray. P-273:Avoid release to the environment.

