

Technical Data sheet

SODIUM SELENITE GMP

Product Code :352502 SODIUM SELENITE GMP

Formula :Na₂SeO₃

Retest period : 24 months

Standard Grade : PE

Rev.: 26/02/2020

According to monographs :PH.EUR.10ED.

General Information :

Mol weight	172,94 g/mol
CAS Nr	10102-18-8
C.E.E. Nr	034-002-00-8
EINECS Nr	233-267-9
HS code	28429010

Transport :

ADR/RID Class	6.1/I,T5
UN Nr	2630
Danger	66
Transport Labels	6.1 N
IMDG Code	6.1/I
IATA Code	6.1
IATA Group	I
CAO Code	673
PAX Code	666

Specifications :

Identification A	Passes test	Identification B	Passes test
Identification C	Passes test	Identification D	Passes test
Assay(Iodim.,dried basis)	98,5 - 101,5 %	Appearance of solution	Passes test
Chloride (Cl)	Max. 50,0 ppm	Loss on drying at 130°C	Max. 0,5 %
pH disolución al 10%	9,8 - 10,8	Sulfates and selenates	Max. 300,0 ppm
Iron (Fe)	Max. 50,0 ppm	Arsenic (As)	Max. 1,0 ppm

Labels : H-300:Fatal if swallowed. H-331:Toxic if inhaled. H-317:May cause an allergic skin reaction. H-411:Toxic to aquatic life with long lasting effects. H-EUH031:Contact with acids liberates toxic gas. P-260:Do not breathe dust/fume/gas/mist/vapours/spray. P-280:Wear protective gloves/protective clothing/eye protection/face protection. P-301+310:IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P-303+361+353:IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P-305+P351+P338:Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P-501:Dispose of contents/container in accordance with local/regional/national/international regulations,

