

Technical Data sheet

SODIUM SELENITE GMP

Product Code :352514 SODIUM SELENITE GMP

Formula :Na₂SeO₃

Retest period : 24 months

Standard Grade : PH

Rev.: 17/04/2017

According to monographs :PH.EUR. 9ED.

General Information :

Mol weight 172,94 g/mol
 CAS Nr 10102-18-8
 C.E.E. Nr 034-002-00-8
 EINECS Nr 233-267-9
 HS code 28429010

Transport :

ADR/RID Class 6.1/I,T5
 UN Nr 2630
 Danger 66
 Transport Labels 6.1 N
 IMDG Code 6.1/I
 IATA Code 6.1
 IATA Group I
 CAO Code 673
 PAX Code 666

Specifications :

Identification A	Passes test	Identification B	Passes test
Identification C	Passes test	Identification D	Passes test
Assay(Iodim.,dried basis)	98,5 - 101,5 %	Appearance of solution	Passes test
Chloride (Cl)	Max. 50,0 ppm	Loss on drying at 130°C	Max. 0,5 %
pH disolución al 10%	9,8 - 10,8	Sulfates and selenates	Max. 300,0 ppm
Iron (Fe)	Max. 50,0 ppm		

Labels : H-300:Fatal if swallowed. H-330:Fatal if inhaled. H-EUH031:Contact with acids liberates toxic gas. H-315:Causes skin irritation. H-317:May cause an allergic skin reaction. H-319:Causes serious eye irritation. H-411:Toxic to aquatic life with long lasting effects. P-301+310:IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P-304+340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P-280:Wear protective gloves/protective clothing/eye protection/face protection. P-261:Avoid breathing dust/fume/gas/mist/vapours/spray. P-273:Avoid release to the environment.

